

# Requisition

[Back to list of main tables](#)



- internal name: requisition
- was "name\_stock\_history" up to & including version 3.5. "Requisition" from version 3.6

| Field name               | Description  | Type   | Ind |
|--------------------------|--|--------|-----|
| custom_data              | Contains any custom values set for a requisition. Key "reporting_period_size" (values "month" or "quarter") contains the size of reporting period the requisition is for                         | Object |     |
| comment                  | Comment for the entire requisition (response type will show the request number here)   | text   |     |
| date_entered             | The date the customer's data was entered   | Date   |     |
| date_order_received      | Date the order reached your premises (from the customer)   | Date   |     |
| date_stock_take          | The date the customer recorded the stock on hand data at their store   | Date   |     |
| daystosupply             | The number of days stock they should be given  | long   |     |
| <b>ID</b>                | The unique ID of this record   | UUID   | *   |
| linked_purchase_order_id | The unique ID of the purchase order related to the request   | UUID   |     |
| linked_requisition_id    | The unique ID link to the request requisition (case type is response)  | UUID   |     |
| <b>name_ID</b>           | The name ID of the other party of the request (supplier) or response (customer)  | UUID   | *   |
| nsh_custinv_ID           | The ID of the customer invoice created from this record  | UUID   |     |
| previous_csh_id          | The ID of the requisition that was submitted before this one   | UUID   |     |
| requester_reference      | Text with the serial_number of other store requisition (case type is response)   | text   |     |
| serial_number            | Next sequence number to be used for virtual on next requisition  | long   |     |
| status                   | The status of the record <b>SG</b> = suggested<br><b>CN</b> = confirmed<br><b>FN</b> = finalised<br><b>WP</b> = web: still in progress<br><b>WF</b> = finalised by customer after web submission | text   |     |
| store_ID                 | The ID of the store the order belongs to (request) or ID of the supplying store (response)   | UUID   |     |

| Field name | Description   | Type  | Ind |
|------------|---|-------|-----|
| type       | <b>im</b> for imprest (where each item has a pre-determined max quantity and the facility submits their current stock on hand) or<br><b>sh</b> for stock history, where the facility submits stock on hand, and their history is used to determine a supply quantity<br><b>request</b> A request from a facility where they determine the quantity. If between facilities, duplicate supply requisition is created on finalisation in the supplying store<br><b>response</b> A response to the request created for the supplying store<br><b>supply</b> the supplying store's copy of a request requisition<br><b>report</b> A requisition that is for reporting purposes only. | Alpha |     |
| user_ID    | The ID of the user who entered the data   | UUID  |     |

## Requisition Line

- Contains all the lines on a requisition
- internal name: requisition\_line
- was "nsh\_line" up to and including version 3.5

| Field name                 | Description  | Type | Ind |
|----------------------------|--|------|-----|
| actualquan                 | quantity to be supplied  | real |     |
| adjusted_consumption       | A consumption value for an item adjusted for days out of stock   | real |     |
| colour                     | colour of the row when displayed   | long |     |
| comment                    | Comment per each line  | text |     |
| Cust_loss_adjust           | Records any losses or gains in stock levels that aren't normal consumption/receipts.   | real |     |
| Cust_prev_stock_balance    | the stock on hand at the previous stocktake (calculated)   | real |     |
| Cust_stock_order           | The calculated amount of stock to give the user.   | real |     |
| Cust_stock_received        | The amount of stock received by customer between previous requisition record for this item and the current stocktake (calculated). | real |     |
| daily_usage                | ID of the record   | UUID | *   |
| <b>ID</b>                  | ID of the record   | UUID | *   |
| imprest_or_prev_quantity   | Imprest quantity defined for each item for the user.   | real |     |
| <b>item_ID</b>             | ID of the item this line is for  | UUID | *   |
| linked_requisition_line_id | ID of the same requisition_line on the request (for response requisition_lines)  | UUID |     |
| line_number                | The saved row number for ordering items in the requisition. (1,2, etc)   | long |     |
| previous_stock_on_hand     | the previous amount of stock on hand on the customer store   | real |     |
| <b>requisition_ID</b>      | ID of the <b>requisition</b> record this record is related to (see above)  | UUID | *   |
| stock_on_hand              | the stock the customer reported for this item this stocktake   | real |     |
| suggested_quantity         | the amount of stock suggested for the customer to order  | real |     |

From:

<https://docs.msupply.org.nz/> - mSupply documentation wiki

Permanent link:

[https://docs.msupply.org.nz/tables\\_fields:main\\_tables:requisition](https://docs.msupply.org.nz/tables_fields:main_tables:requisition)

Last update: **2020/01/07 01:04**

